

Shoulder-Borne Carrying Straps, Carrying Strap Assemblies
and Golf Bags Incorporating the Same

Field of the Invention

5 The present invention relates to carrying straps, carrying strap assemblies, and, more particularly, to carrying straps with enhanced tension configuration. This invention also relates to a dual strap carrying assembly which can be converted into a single strap carrying assembly of a non-symmetrical design for carrying a load on either the left or the right shoulder of a carrying person. More specifically, although of course
10 not solely limiting thereto, this invention also relates to carrying straps and carrying strap assemblies for golf-bags and other bags as well as golf bags provided with the same.

Background of the Invention

15 Shoulder-borne carrying straps are generally provided for use with bags, sacks, rucksacks, boxes or containers to assist a person to carry bulky, heavy or both bulky and heavy articles or items from one place to another. Shoulder straps are preferred over hand-carrying straps because the weight can rest on the shoulder ridge of the carrying person, thereby freeing the hands of the carrying person for other purposes
20 such as attaining body balance or for self protection.

The dual shoulder loop and the single shoulder loop carrying strap systems are the two common types of shoulder carrying systems. The single shoulder loop carrying strap system (hereinafter referred to as the "single strap" system for succinctness and
25 convenience) generally includes a length of strap having both its longitudinal ends attached to the load, thereby forming a loop of a carrying strap. In use, a person inserts one of his arms through the loop until the shoulder-engaging portion of the strap rests on the shoulder ridge of the carrying person and then lifts the load by his shoulder. In such an application, the load is usually carried on one side of the body
30 and the load is usually borne by either shoulder on that side of the carrying person,

depending on personal preferences. A typical example of a single strap system is shown, for example, in US Patent No. 5,735,398 to Price.

Since a single strap carrying system is usually used to carry a load on one side of the carrying person, a well-designed shoulder strap usually includes a padded shoulder engaging portion having a larger width than the rest of the strap to distribute weight. In a typical well-designed carrying strap, the shoulder engaging portion is usually slightly curved or has an overall parabolic shape so that the portion of the strap between the load and the shoulder engaging portion can smoothly and gradually extend towards the outside of the body without propping up the outer edge of the shoulder engaging portion.

Thus, a typical single carrying strap is usually characterised by a length-wise non-symmetrical shoulder engaging portion which is designed to accommodate the transversal shape of the shoulder ridge for user comfort as well as to mitigate the tendency of the strap to slip off the shoulder due to the overhanging load.

Because of its non-symmetry, a single strap for a load having specific orientations such as golf bags is usually adapted for use on either the left- or the right- shoulders so that different straps are needed for the left- and the right- shoulders. Hence it will be advantageous to provide carrying straps with improved user friendliness such that the single straps can be used on either shoulders.

While the single strap system is convenient for moving a load for a short distance, it is not particularly preferable for moving a heavy load for a longer distance because the strap load is localised on one shoulder ridge and this may hurt the carrying person. This is particularly so when the load being carried is a fully-loaded golf bag having an open end with a lot of loosely placed golf clubs which may jiggle, jump or bounce when the carrying person moves.

To enhance the comfort of the carrying person, a dual shoulder-loop carrying system (hereinafter referred to as the "dual strap" system for succinctness and convenience) is usually utilized. The dual strap system generally includes two strap loops which are formed by attaching two loops of carrying straps to a load. The shoulder loops are generally designed so that the arms of the carrying person are inserted through the loops until the shoulder engaging portions on the two strap loops rest squarely on the shoulder ridges of the carrying person's. Furthermore, in the dual strap systems, the weight of the load is usually quite evenly distributed across the two shoulders and the load is usually maintained near the middle of the back of the carrying person.

Common examples of applications of a dual strap system includes back-packs, rucksacks, baby carriers and golf-bags. Examples of such dual strap systems which have been particularly utilized in golf bags include US Patent Nos. 5,042,704, 5,558,258 and 6,173,874 to Izzo, US Patent No. 5,954,255 to Beebe et al., US Patent No. 6,006,974 to Varney et al., and US Patent No. 6,173,874 to Stein et al.

While a dual strap system provides enhanced comfort due to a substantially balanced weight distribution on both shoulders, the harness-like structure of a dual strap system makes it more tedious to mount and more difficult to dismount than a single strap system. Dismounting a dual strap system is more difficult because the straps usually converge towards the load and, as a result, the tension in the straps tends to pull the straps towards each other while dismounting requires pushing of the strap pair away from each other in order to remove them from the shoulder ridges.

In order to avoid the tediousness and difficulty associated with the mounting and dismounting of a load, when using a dual strap system, many people prefer to use a single strap system for moving a load for a short distance, for example, when carrying a fully-load golf-bag between hits, and, to use a dual strap system when carrying the load for a long distance. To accommodate the different usages, some golfers carry both a dual strap and a single strap system in their golf set so that the carrying systems can be used alternatively.

Thus, it will be advantageous if there can be provided carrying straps or strap carrying systems which can be convertible between a dual strap system and a single strap system as and when necessary so that a user does not have to carry two different sets of carrying straps. It will be more advantageous if such a strap system can be easily and conveniently convertible between the two forms without compromising the comfortability of the dual strap system while at the same time even possibly enhancing the comfortability of the resultant single strap system. Furthermore, it will be further advantageous if there can be provided a dual strap carrying system of the afore-said describe which can be convertible into a non-symmetrical single strap system which is equally well adapted for use both on the left or the right shoulders.

Also, it will be highly advantages if there can be provided an improved carrying strap with improved characteristics to alleviate its tendency to slip off the shoulder.

However, there are several conflicting requirements which need to be overcome, or at least alleviated, in order to provide a strap carrying system having the aforesaid-advantages or benefits. For example, since the load carried by a dual strap system tends to pull the two strap members towards each other, there is generally no need to prevent un-intentional slipping off of the straps from the shoulders. As a result, the shoulder engaging portions of the two member straps usually include a non-frictional shoulder engaging surface so that the member straps can be easily pushed away from each other and from their respective contacting shoulder ridges for dismounting.

On the other hand, a load carried by a single strap system is usually disposed on one side of the body and tends to pull the shoulder engaging portion of the strap away from the body and towards a disengaging position. To alleviate undesirable slippage of the shoulder ridge, the shoulder engaging portion of the strap member is usually provided with a non-slippery or frictional shoulder engaging surface together with a non-symmetrical transversal shape along its length.

Hence, it will be desirable if there can be provided improved carrying straps or carrying strap assemblies which provide at least some of the aforesaid benefits or advantageous while overcoming, or at least accommodating, the afore-said conflicting requirements.

Object of the Invention

In light of the above, it will be appreciated that there is a continuing and long-awaited need for improved carrying straps and carrying strap assemblies which substantially achieve the aforesaid benefits while fulfilling the afore-said conflicting requirements.

In particular, there exists a demand for an improved single carrying strap having improved tension characteristics to alleviate its tendency to slip off the shoulder.

Therefore, it is an object of the present invention to provide improved carrying straps which have improved tension configuration and characteristics to help the strap to stay on the shoulder ridge so that a user does not have to restore the strap frequently.

It is an object of the present invention to provide improved carrying straps which have improved tension configuration and characteristics to help the strap to stay on the shoulder ridge so that a user does not have to restore the strap frequently.

Accordingly, it is an object of the present invention to provide carrying straps or a strap carrying assembly which can be configured as a dual strap carrying system or, alternatively, as a single strap system without compromising their benefits.

It is another object of the present invention to provide carrying straps and strap carrying system which can be configured either as a dual strap carrying system or a

single strap system having a non-symmetrical strap member which can be used on other sides of the shoulders of the carrying person.

As a minimum, it is an object of the present invention to provide the public with a choice of an improved carrying strap or a strap carrying system having improved tension characteristics. It is yet a further object of this invention to provide a strap assembly in which both the non-symmetric strap members of the dual strap system can be utilized to form part of the non-symmetrical single strap system so that both straps can be utilized effectively. It is at least an object of this invention to provide an improved carrying strap for the choice of the public.

Summary of the Invention

In view of the afore-said, there is provided in one broad aspect of the present invention a carrying strap including a shoulder-engaging portion disposed between a first and a second longitudinal strap ends, said shoulder-engaging portion includes a strap length of a first curvature, wherein said shoulder-engaging portion is connected to each said longitudinal strap end via a curved strap portion of a second curvature, said second curvature being substantially opposite to said first curvature.

Preferably the shoulder-engaging portion includes a retracted portion for fitting between the neck and the shoulder edge of the carrying person.

Preferably, the shoulder-engaging portion includes a concave side of said first curvature extending intermediate between said longitudinal ends, the ends of said concave side are connected to said longitudinal ends respectively via the convex side of said strap portions of said second curvature.

Preferably, one side of the strap extending between said longitudinal ends include alternate protracted and retracted strap portions.

Preferably, the strap includes alternate shoulder engaging surfaces having dissimilar frictional characteristics.

Preferably, the shoulder strap portion generally forms a rounded W-shape between said longitudinal ends.

Preferably, the strap includes a plurality of strap portions resembling the shape of a boomerang.

- 5 Preferably, the shoulder strap portion includes two boomerang-shape portions connected in series.

In another broad aspect of the present invention, there is provided a carrying strap including a shoulder-engaging portion disposed between a first and a second longitudinal strap ends, said shoulder-engaging portion includes a retracted portion, wherein a first and a second strap portions of similar curvature are disposed respectively between said shoulder engaging portion and said first and second longitudinal ends.

- 10
15 In order to enhance comfortability of single strap carrying system obtained from conversion of a dual strap system, it is preferred that the single strap carrying system includes the back-to-back fastening of strap members of the dual strap carrying system so that a doubly cushioned single strap system can be formed to enhance comfortability and, at the same time, none of the strap members of the dual strap system has to be stored when converted into the single strap system.

- 25 According to another aspect of the present invention, there is provided a carrying strap assembly including a first and a second elongated strap members which are connectable to a load via detachable connecting means, said strap members have a first set of shoulder engaging surfaces for engaging the left and right shoulders of a carrying person when said straps are configured as a dual shoulder-loop carrying strap system, wherein each said shoulder engaging surface is non-symmetrical about its longitudinal centre line and said first set of shoulder engaging surfaces are substantially mirror symmetrical to each other and said shoulder engaging surfaces are

detachably fastenable to each other so that both shoulder engaging surfaces are substantially mutually overlapping.

5 Preferably, the first and said second strap members are connectable near the ends by a detachable connecting means.

Brief Description of the Drawings

10 Preferred embodiments of the present invention will now be explained in further detail by way of example and with reference to the accompanying drawings, in which:-

Fig. 1 shows an example of a dual strap carrying system formed by an assembly of a left and a right strap members.

15 Fig. 2 shows the top plan view of the left strap member and having the non-slippery shoulder engaging surface for exposed,

Fig. 3 shows the bottom view of the left side strap member of Fig. 2 with the slippery shoulder engaging surface fully exposed,

Fig. 4 shows, for example, an application of the dual strap carrying system,

Fig. 5 shows another example illustrating the use of the dual strap carrying system,

20 Fig. 6 illustrates schematically the directions and description of force within the dual strap systems,

Fig. 7 illustrates schematically a carrying person dismounting the dual strap carrying system,

Fig. 8 illustrates schematically the direction of force along a single strap system,

Fig. 9.a to 9.e illustrate the exemplary steps for converting a dual strap system into a single strap system by separating the strap members and recombining the non-symmetrical strap members into a single strap carrying system,

Fig. 10 schematically illustrates a carrying person carrying a golf bag on one side of his body using the single strap system,

Fig. 11 shows the spatial relationship between the cushioned shoulder engaging portion of the strap member and the shoulder ridge of the carrying person when the strap is gripping on the left shoulder, and

Fig. 12 shows a carrying person carrying a golf bag using a single strap system on the right shoulder of the carrying person.

Detailed Description of the Preferred Embodiments

Referring firstly to the Figures, especially Figures 1 and 9.a, there are shown strap members (10, 20) of a first embodiment of the present invention which are assembled and configured as a dual strap carrying system (30) or assembly of a second embodiment of the present invention. The dual strap carrying system (30) includes a first (10) and a second (20) strap members which are assembled together and configured as a dual strap carrying system by connecting their corresponding longitudinal ends (11, 21) to the load, for example, a golf bag, via a swivel connector (40) for further enhanced comfort. Each of the strap members is generally a shoulder strap having two ends for attaching to a load and the straps are designed so that they can be used as a stand-alone carrying strap as and when required. At the same time, both straps can be assembled to form a combined single strap in a manner to be explained in further details below.

Referring to Figures 2 and 3, there are shown the top and bottom plan views of the first strap member which are delineated by two substantially elongated and rounded W-shape edges on its lateral sides. The first strap member (10) of Figure 2 includes a shoulder engaging portion (12) having a first shoulder engaging surface (13) which is

defined between a concave peripheral side (14) and a convex (15) peripheral side. The shoulder engaging portion (12) is connected to both longitudinal ends (11, 19) of the carrying strap (10) via two intermediate strap portions (16, 17). Each intermediate strap portion includes a convex lateral side which joins to the concave side of the shoulder-engaging portion.

An alternative second shoulder-engaging portion (18) is disposed on the back of the first engaging surface (13). It is preferred that the two alternative surfaces have dissimilar shoulder engaging characteristics for applications to be described below. In this embodiment, it is preferred that the first engaging surface (13) is substantially frictional or non-slippery.

The shoulder-engaging portion (12) is connected to the other adjacent intermediate strap portions with the longitudinal ends of its concave portion connecting to the convex portions of the adjacent strap portions and with the longitudinal ends of its convex portion connecting to the concave portions of the adjacent strap portions.

As shown more specifically in Figures 2 and 3, it will be observed that the convex side of the curved shoulder-engaging portion connects with the concave sides of the adjacent intermediate connecting strap portions while, at the same time, the concave side of the shoulder-engaging portion connects with the convex side of the adjacent intermediate connecting strap portions.

In other words, the strap member (10) includes a shoulder-engaging portion having a curvature which is connected to adjacent intermediate strap portions having a substantially opposite curvature. With this arrangement, the strap member (10) of this specific design has a substantially rounded W-shape between its longitudinal ends. Alternatively, this strap member (10) can be described as including a retracted portion for resting between the neck and the arm of the carrying person and that retracted portion is disposed intermediate between two adjacent protruding portions.

Referring now to Figures 8, 10, 11 and 12, there are shown examples of how this strap member (10) can be used a single strap carrying system. It will be observed that, when the strap member is used as a single strap carrying system, the load overhangs the side of the body of the carrying person. In such a use, the shoulder-engaging surface (13) rests on the shoulder ridge of the carrying person and the adjacent strap portions will respectively overhang on the front and rear parts of the person.

Due to the curvatures of the shoulder-engaging portion (14) and the adjacent connecting strap portions, the front and rear overhanging portions of the strap member form a curvature overhanging the front and rear part of the body. This curvature resembles the shape of a boomerang with the first (upper) limb adjoining the shoulder-engaging portion (12) extending towards the body of the carrying person and the second, lower or distal, limb extending away from the body and towards the load as shown in the Figures.

When a load is attached to the longitudinal strap ends (11, 19) and overhangs the right side of the carrying person, the gravitational weight of the load causes the strap members to be taut and pulls the intermediate strap portions downward. Due to the curvature of the intermediate strap portion, downward tension on the lower-half (lower or distal limb) of the intermediate strap portion causes resultant inward tension in the upper-half (first limb) of the intermediate strap portion which will pull the shoulder-engaging portion (12) towards the neck of the carrying person, thereby substantially mitigating or counter balancing the tendency to slip off the shoulder.

To further mitigate the tendency to slip off the shoulder, the shoulder-engaging surface is preferably provided with a non-slippery surface, for example, by adding a frictional layer of a matted or meshed surface to enhance engagement between the loaded strap and the shoulder.

Referring to Figures 11 and 12, it can be seen that the shoulder-engaging portion of the single strap member is worn so that its concave lateral side (14) juxtaposes the neck so that the concave portion substantially follows the shape of the trapezius muscle for the carrying person's comfort. To further enhance the carrying person's comfort, a cushioning pad (shown within the broken lines) is included in the shoulder-engaging portion. In addition, the shoulder-engaging portion may include a resilient or elastomeric substance embedded between the two alternative shoulder-engaging surfaces for further comfort.

In order to provide a strap member of a similar design for use as a carrying strap on the left shoulder, there is provided a second strap member which has a general mirror symmetry to that of the first, or right-shoulder, strap member. In general, the second strap member (20) also includes a shoulder engaging portion having a first shoulder engaging surface which is defined between a concave peripheral side and a convex peripheral side. The shoulder engaging portion is connected to both longitudinal ends of the carrying strap via two intermediate strap portions. Each intermediate strap portion includes a convex lateral side which joins the concave side of the shoulder-engaging portion. Similarly, the strap member can be described as including a shoulder-engaging portion having a curvature which is connected to adjacent strap portions having a substantially opposite curvature. With this arrangement, the strap member of this specific design has a substantially rounded W-shape between its longitudinal ends.

In order to provide a universal strap for both shoulders, the strap member is designed so that the intermediate connecting portions are substantially symmetrical about the centre portion of the shoulder-engaging portion. With such an arrangement, the shoulder strap can be rotated 180 degrees about its longitudinal centre and become a shoulder strap for the other shoulder and used in a manner as shown in Figure 12.

It will be appreciated that while a retracted portion to accommodate the contour of the trapezius muscle is desirable for enhanced comfort, such a retraction is not strictly

necessary. Improved tension characteristics to help a single strap to stay on the shoulder will be accomplished by providing curved intermediate portions between the shoulder engaging portion and the longitudinal ends such that the intermediate portions have a convexly curved portion which convexes towards the centre of the body and away from the carrying side of the body during normal use.

In Figure 4, a left- and a right- strap members are shown to be used together with their longitudinal ends attached to a load to form a dual strap system. With this configuration, the load can be shared between the two shoulders and the carrying person's comfort will be enhanced.

Figure 5 shows another example of a dual strap assembly in which the corresponding longitudinal ends (11, 21) of the left- and right- straps, i.e., the longitudinal ends overhanging the rear part of the carrying person, are connected firstly to a swivel connector and then to the load. This swivel connector serves to enhance the comfort of the carrying person by making differential weight adjustment as explained, for example, in the co-pending Patent Application Serial No. 09/756,709. In this arrangement, the corresponding longitudinal ends of the left- and right- strap members are detachably attached to each other by the detachable members of the swivel connector (40).

When used as a dual strap assembly as shown in Figures 5 and 6, the arrows shown in Figure 6 indicate the direction of the tension on the straps when attached to a load. It will be observed that the weight of the load will cause the upper portion of the strap members, which are disposed immediately adjacent the shoulder-engaging portions (12, 22), to pull towards each other.

In this configuration, due to the convergence of the strap tensions on the upper part of the carrying strap portions, there is only minimal concern that the strap members will slip off the shoulders. In order to enable easy dismounting of the dual strap carrying

system, it is preferred that the shoulder-engaging surfaces are made with a slippery or non-frictional surface so that it can be easily slid off the shoulder as and when desired by the user, as illustrated in Figure 7.

5 Referring to Figure 9.a-9.e, there are shown the various steps of separating the dual strap assembly and combining the left and right strap members together to form a single strap carrying system comprising the two strap members. The strap members (10, 20) are fastened together by fastening means distributed on the slippery surface of each strap member. Thus, the combined single strap member will have non-
10 slippery surfaces on both sides. It will be observed from Figures 9.a to 9.e that the two strap members are substantially of mirror symmetry to each other. At the same time, the upper and the lower portions of each strap member are substantially symmetrical to each other about the middle of the respective shoulder-engaging portions. In addition, the fastening means may be distributed on the slippery surface of the strap members in a substantially mirror-symmetrical way so that when the
15 straps are combined, they will overlap with each other. The assembly of a single strap carrying system by combining two shoulder member straps provides a single strap system of enhanced comfort because of increased thickness. Furthermore, because of the symmetry, each of the member strap as well as the combined single strap assembly can be used either on the left or the right shoulder so that there is no need to carry a
20 strap member as a load.

In the above specification, while examples of strap members and assemblies of strap members have been described with references to the drawings with accompanying
25 illustrations of the usage and application, it should be appreciated that these examples are provided to assist understanding and illustration of the present invention only and should not be construed as intending to restrict the scope or application of the present invention.

As a minimum, it shall be appreciated that trivial modifications or variations made on
30 the basis of the embodiments described in the present specification in light of common general knowledge are within the scope and spirit of the present invention.

Furthermore, it should be appreciated that the scope of the present invention should not be limited to the literal meaning of the claims but, instead, should be construed according to the essence and spirit of the invention as described and interpreted in accordance with the present specification.

5

In addition, the term curvature has been used in the present specification to describe an out-line which is non-linear and which substantially follows the shape of a conventional rounded curve. However, this is not restricted to a rounded curve and will include a portion which has an overall retracted or protruding outline which may, for example, be generally formed by an ensemble of straight or curved lines into an overall curved shape.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206